



- Ελαστική πολυουρεθάνη
- Ζάντα από ενισχυμένο ντουραλουμίνιο
- Ρουλεμάν άξονα:

☐☐ σφαιρικό [S]



- Elastic polyurethane
- Reinforced aluminum center
- Axle bearing:

☐☐ ball [S]



						CODE
100	40	12	40	☐☐	300	WL-100-AOE.S12
	40	15	40	☐☐	300	WL-100-AOE.S15
100X	50	20	60	☐☐	380	WL-100X-AOE.S20
125	40	20	50	☐☐	350	WL-125-AOE.S20
	40	25	50	☐☐	350	WL-125-AOE.S25
125S	50	20	60	☐☐	450	WL-125S-AOE.S20
160	50	20	60	☐☐	600	WL-160-AOE.S20
	50	25	60	☐☐	600	WL-160-AOE.S25
180	50	20	60	☐☐	670	WL-180-AOE.S20
	50	25	60	☐☐	670	WL-180-AOE.S25
200	50	20	60	☐☐	700	WL-200-AOE.S20
	50	25	60	☐☐	700	WL-200-AOE.S25
230	50	20	60	☐☐	800	WL-230-AOE.S20
	50	25	60	☐☐	800	WL-230-AOE.S25
250	50	20	60	☐☐	800	WL-250-AOE.S20
	50	25	60	☐☐	800	WL-250-AOE.S25