


**Load Capacity: 70kg, for speed up to 4km/h  
(According to EN 12530)<sup>oo</sup>**

|   |   |                                |  |                               |
|---|---|--------------------------------|--|-------------------------------|
|  | PRODUCTION OF INSTITUTIONAL CASTORS AND WHEELS<br>THESSALONIKI - GREECE   |                                | PERMIS. VARIATIONS:  | PART No:                      |
|   | This drawing is the property of RODA S.A. It must neither be reproduced in any manner nor shall it be submitted to third parties or competitors without our written consent |                                | SURFACE FINISH :   | UNF . DIM.:                   |
| DESIGNED 17/7/2013 E.POLIMEROPOULOU   | DRAWN 17/7/2013 E.POLIMEROPOULOU  | CHECKED 17/7/2013 H.SAATSOGLOU | PART NAME :  | <b>S.075.CPA.TSG</b>          |
| C3<br>B2<br>A1<br>A/A   | QUANTITY<br>REPLACE :   | SCALE                          | PART DESCRIPTION :<br><b>Swivel castor, steel support, top plate fitting.Wheel 75x32mm,electric conductive non marking grey rubber (82shA) plain bearing</b> | DRAWING NUMBER :<br>SHEET No. |
|   |   |                                | GEN. DWG. NUM. :   |                               |